

International Attachments USA Solar / Guardrail Track Models 3030- Rocky Point Drive W.

Tampa, Florida 33607/ Email; info@iai-usa.com

Toll free: 1-877-219-1962

TECHNICAL SPECIFICATION FOR 600

- INO Solar Model 600
- Track drive (2 Speed)
- 38 kW Perkins 403J-E17T Turbocharged EU stage V
- Hammer 1000j (Hydraulic)
- Max post size- 200mm x 200mm
- Hydraulic side shift 150mm left & light
- Hydraulic tilt +/- 150

8 feet mast

- Two-Stage Mast
- GPS compatible
- Including tools, manuals, and spare oil filters.
- All the machine's specifications are shown on the product sheet.
- The warranty is 12 months on parts and quality.
- H/S Code 8430-10-00
- Weight 2250 kg
- Machine color Caterpillar yellow



TECHNICAL SPECIFICATION FOR 800

- INO Solar Model 800
- Track drive (2 Speed)
- 38 kW Perkins 403J-E17T Turbocharged EU stage V
- Hammer 1000j (Hydraulic)
- Max post size- 200mm x 200mm
- Hydraulic side shift 150mm left & light
- Hydraulic tilt +/- 15o
- 10 feet mast
- Two-Stage Mast
- GPS compatible
- Including tools, manuals, and spare filters.
- All the machine's specifications are shown on the product sheet.
- The warranty is 12 months on parts and quality.
- H/S Code 8430-10-00
- Weight 3000 kg
- Machine color Caterpillar yellow



TECHNICAL SPECIFICATION FOR 1000

- INO Solar Model 1000
- Track drive (2 Speed)
- 38 kW Perkins 403J-E17T Turbocharged EU stage V
- Hammer 1250j (Hydraulic)
- Max post size- 200mm x 200mm
- Hydraulic side shift 150mm left & light
- Hydraulic tilt +/- 150

15 feet mast

- Two-Stage Mast
- GPS compatible
- Including tools, manuals, and spare filters.
- All the machine's specifications are shown on the product sheet.
- The warranty is 12 months on parts and quality.
- H/S Code 8430-10-00
- Weight 4000 kg
- Machine color Caterpillar yellow



TECHNICAL SPECIFICATION FOR 1200

- İNO Solar Model 1200
- Track drive (2 Speed)
- 36 kW Perkins 403J-E17T Turbocharged EU stage V
- Hammer 1450j (Hydraulic)
- Max post size- 200mm x 200mm
- Hydraulic side shift 150mm-left & light
- Hydraulic tilt +/- 15°
- 20 feet mast
- Two-Stage Mast
- GPS compatible
- Including tools, manuals, and spare oil filters.
- All the machine's specifications are shown on the product sheet.
- The warranty is 12 months on parts and quality.
- H/S Code 8430-10-00
- Weight 4800 kg
- Machine color Caterpillar yellow



TECHNICAL SPECIFICATION FOR 1400

- Challenger Solar Model 1400
- Track drive- 2 Speed
- Fifth Wheel- 360° Rotation
- 55 KW Perkins 404J-E22TA Turbocharged EU stage V, US EPA Tier 4 Final Water-cooled engine
- Hammer 1450 Joule (Hydraulic)
- Max. Post Height- 26 feet
- Max post size- 200x200 mm, Ø350 (Round Pipes)
- Hydraulic side shift- 150mm (Left-Right)
- Hydraulic tilt +/- 15°
- Mast Type- Two-Stage
- GPS Compatible
- Including tools, manuals, and spare oil filters.
- All the machine's specifications are shown on the product sheet.
- The warranty is 12 months on parts and quality.
- H/S Code 8430-10-00
- Weight 6900 kg
- Machine color Caterpillar yellow





